

HT321 - HT322 - HT326 - HT327

CAT IV DIGITAL PROFESSIONAL MULTIMETER

HT320 digital multimeter series provides all the essential features in compact and easy-to-use instruments developed for every-day use. Rugged design and accurate measurements make HT320 digital multimeter series the ideal choice for electricians, HVAC technicians, etc. both for maintenance and troubleshooting.

FUNCTIONS	HT321	HT322	HT326	HT327
TRMS measurements				•
AC Voltage	•	•	•	•
DC Voltage	•	•	•	•
AC Current			•	•
DC Current			•	•
Resistance	•	•	•	•
Continuity test	•	•	•	•
Frequency			•	•
Capacitance			•	•
Duty Cycle			•	•
Diode test	•	•	•	•
Data HOLD	•	•	•	•
Temp. with type K probe		•		
MAX/MIN	•(Max)	•(Max)		•
PEAK				•
Relative measurements			•	•
Manual range	•	•	•	•
Backlight		•	•	•
Bargraph				•
AutoPowerOff	•	•	•	•

GENERAL SPECIFICATIONS

Display:	LCD, 3½ dgt, 1999 points (HT321-HT322) LCD, 3¾ dgt, 3999 points (HT326) LCD, 4 dgt, 3999 points (HT327)
Power supply:	2x1.5V bat. type AA LR6 (HT321-HT322-HT326), 1x9V bat. type IEC6F22 (HT327)
Battery life:	approx 220 hours
Safety:	IEC/EN61010-1
Category of measurement	CAT IV 600V – CAT III 1000V
Pollution degree:	2
Insulation:	double insulation
Max height of use:	2000m
Dimensions (LxWxH):	163x88x48mm
Weight (batteries incl.):	280g, 400g (HT327)

TECHNICAL SPECIFICATIONS	HT321	HT322	HT326	HT327
DC Voltage				
Measurement range:	0.2mV ÷ 600V	0.2mV ÷ 600V	0.2mV ÷ 600V	0.1mV ÷ 1000V
Basic accuracy:	±(0.8%rdg + 1dgt)	±(0.8%rdg + 1dgt)	±(0.8%rdg + 2dgt)	±(0.5%rdg + 2dgt)
AC Voltage				
Measurement range:	0.2mV ÷ 600V	0.2mV ÷ 600V	0.1mV ÷ 600V	0.1mV ÷ 750V
Basic accuracy:	±(1.5%rdg + 3dgt)	±(1.5%rdg + 3dgt)	±(1.0%rdg + 3dgt)	±(1.0%rdg + 3dgt)
DC Current				
Measurement range:			0.01A ÷ 10A	0.1µA ÷ 10A
Basic accuracy:			±(1.2%rdg + 3dgt)	±(1.2%rdg + 3dgt)
AC Current				
Measurement range:			0.01A ÷ 10A	0.1µA ÷ 10A
Basic accuracy:			±(2.0%rdg + 5dgt)	±(1.2%rdg + 5dgt)
Resistance and continuity test				
Measurement range:	0.1Ω ÷ 20MΩ	0.1Ω ÷ 20MΩ	0.1Ω ÷ 40MΩ	0.1Ω ÷ 40MΩ
Basic accuracy:	±(1.0%rdg + 3dgt)	±(1.0%rdg + 3dgt)	±(1.0%rdg + 2dgt)	±(0.8%rdg + 2dgt)
Buzzer:	<120Ω	<120Ω	<140Ω	<35Ω
Frequency				
Measurement range:			0.01Hz÷99.99kHz	1Hz÷40.00kHz
Basic accuracy:			±(1.5%rdg + 5dgt)	±(0.1%rdg + 2dgt)
Capacitance				
Measurement range:			0.001nF ÷ 100µF	0.001nF ÷ 100mF
Basic accuracy:			±(3.0%rdg + 5dgt)	±(2.0%rdg + 8dgt)
Duty Cycle				
Measurement range:			20% ÷ 80%	
Basic accuracy:			±(1.0%rdg + 5dgt)	
Temperat. with type K probe				
Measurement range:			-40°C ÷ 800°C	
Basic accuracy:			±(2.0%rdg + 3dgt)	

53

ACCESSORIES	Code
Standard	
Couple of test leads	4413-2
Carrying bag	B80
Batteries	
User manual	
Optional	
Adapter for type K probes (only HT322)	T10
Type K probes (only HT322)	



HT321
HR000321



HT322
HR000322



HT327
HR000327



HT326
HR000326



宇宏企業股份有限公司

台北：三重區重新路五段609巷16號6樓之1 新竹：新竹縣竹北市台元26號4樓之10
TEL:02-22782269 FAX:02-22782059 TEL:03-552-6779 FAX:03-552-6739
http://www.fluke-tekrnix.tw http://www.radiotek.com.tw



1. ELECTRICAL SPECIFICATIONS

Accuracy is indicated as \pm (%rdg + numbers of digits) at $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$, <75%HR

DC VOLTAGE

Range	Resolution	Accuracy	Overload protection
200.0mV	0.1mV	$\pm(0.8\%rdg+1dgt)$	600VDC/ACrms
2.000V	0.001V		
20.00V	0.01V		
200.0V	0.1V		
600V	1V	$\pm(1.0\%rdg+2dgt)$	

Input impedance: 10M Ω

AC VOLTAGE

Range	Resolution	Accuracy (45 ÷ 400Hz)	Overload protection
200.0mV	0.1mV	Not specified	600VDC/ACrms
2.000V	0.001V	$\pm(1.5\%rdg+3dpts)$	
20.00V	0.01V		
200.0V	0.1V		
600V	1V		

Input impedance: 10M Ω

RESISTANCE

Range	Resolution	Accuracy	Open voltage	Overload protection
200.0 Ω	0.1 Ω	$\pm(1.0\%rdg+8dpts)$	about 3.0V	600VDC/Acrms (< 30sec)
2.000k Ω	0.001k Ω	$\pm(1.0\%rdg+3dpts)$		
20.00k Ω	0.01k Ω			
200.0k Ω	0.1k Ω			
2.000M Ω	0.001M Ω			
20.00M Ω	0.01M Ω	$\pm(3.0\%rdg+3dpts)$		

DIODE TEST

Range	Resolution	Open voltage	Overload protection
	1mV	circa 1.5VDC	600VACrms (< 30sec)

Overload protection: 600Vrms

TEST CONTINUITY

Range	Buzzer	Open voltage	Overload protection
	R<120 Ω	about 1.5VDC	600VACrms (< 30sec)

TEMPERATURE WITH TYPE K PROBE

Range	Resolution	Accuracy	Overload protection
-40 $^{\circ}\text{C} \div 1^{\circ}\text{C}$	1 $^{\circ}\text{C}$	$\pm 5^{\circ}\text{C}$	600VACrms (< 30sec)
0 $^{\circ}\text{C} \div 800^{\circ}\text{C}$		$\pm(2.0\%rdg+3dgt)$	
-40 $^{\circ}\text{F} \div 31^{\circ}\text{F}$	1 $^{\circ}\text{F}$	$\pm 9^{\circ}\text{C}$	
32 $^{\circ}\text{F} \div 1382^{\circ}\text{F}$		$\pm(2.0\%rdg+5dgt)$	





2. GENERAL SPECIFICATIONS


Display:

- LCD display, 3 ½ digit with maximum reading 1999 counts with sign and decimal point
- Automatic polarity indication
- Backlight
- "OL" over range indication

Features:

- MAX
- HOLD
- RANGE for manual selection
- Auto Power OFF after 15 minutes of don't work

Low battery indication:

- The symbol "  " appears when the battery voltage is low

Operating temperature:

- -5 °C to 40 °C, <80%HR

Storage temperature:

- -10 °C to 60 °C, <70%HR

General informations:

- Altitude max: 2000m
- Pollution degree: 2
- Insulation: double insulation

Power supply:

- 2 x 1.5V alkaline batteries type AAA MN2400 LR03 AM4

Sizes:

- 163(L)x88(W)x48(H) mm

Weight (included batteries):

- 280g

Applied standards:

- LVD: EN 61010-1 CAT IV 600V – CAT III 1000V
- EMC: EN60326

This product conforms to the prescriptions of the European directive on low voltage 2006/95/EEC and to EMC directive 2004/108/EEC

