

HT321 - HT322 - HT326 - HT327

CAT IV DIGITAL PROFESSIONAL MULTIMETER

HT320 digital multimeter series provides all the essential features in compact and easy-to-use instruments developed for every-day use. Rugged design and accurate measurements make HT320 digital multimeter series the ideal choice for electricians, HVAC technicians, etc. both for maintenance and troubleshooting.

FUNCTIONS	HT321	HT322	HT326	HT327
TRMS measurements				•
AC Voltage	•	•	•	•
DC Voltage	•	•	•	•
AC Current			•	•
DC Current			•	•
Resistance	•	•	•	•
Continuity test	•	•	•	•
Frequency			•	•
Capacitance			•	•
Duty Cycle			•	•
Diode test	•	•	•	•
Data HOLD	•	•	•	•
Temp. with type K probe		•		
MAX/MIN	•(Max)	•(Max)		•
PEAK				•
Relative measurements			•	•
Manual range	•	•	•	•
Backlight		•	•	•
Bargraph				•
AutoPowerOff	•	•	•	•

GENERAL SPECIFICATIONS

Display:	LCD, 3½ dgt, 1999 points (HT321-HT322) LCD, 3¾ dgt, 3999 points (HT326) LCD, 4 dgt, 3999 points (HT327)
Power supply:	2x1.5V bat. type AA LR6 (HT321-HT322-HT326), 1x9V bat. type IEC6F22 (HT327)
Battery life:	approx 220 hours
Safety:	IEC/EN61010-1
Category of measurement	CAT IV 600V – CAT III 1000V
Pollution degree:	2
Insulation:	double insulation
Max height of use:	2000m
Dimensions (LxWxH):	163x88x48mm
Weight (batteries incl.):	280g, 400g (HT327)

TECHNICAL SPECIFICATIONS	HT321	HT322	HT326	HT327
DC Voltage				
Measurement range:	0.2mV ÷ 600V	0.2mV ÷ 600V	0.2mV ÷ 600V	0.1mV ÷ 1000V
Basic accuracy:	±(0.8%rdg + 1dgt)	±(0.8%rdg + 1dgt)	±(0.8%rdg + 2dgt)	±(0.5%rdg + 2dgt)
AC Voltage				
Measurement range:	0.2mV ÷ 600V	0.2mV ÷ 600V	0.1mV ÷ 600V	0.1mV ÷ 750V
Basic accuracy:	±(1.5%rdg + 3dgt)	±(1.5%rdg + 3dgt)	±(1.0%rdg + 3dgt)	±(1.0%rdg + 3dgt)
DC Current				
Measurement range:			0.01A ÷ 10A	0.1µA ÷ 10A
Basic accuracy:			±(1.2%rdg + 3dgt)	±(1.2%rdg + 3dgt)
AC Current				
Measurement range:			0.01A ÷ 10A	0.1µA ÷ 10A
Basic accuracy:			±(2.0%rdg + 5dgt)	±(1.2%rdg + 5dgt)
Resistance and continuity test				
Measurement range:	0.1Ω ÷ 20MΩ	0.1Ω ÷ 20MΩ	0.1Ω ÷ 40MΩ	0.1Ω ÷ 40MΩ
Basic accuracy:	±(1.0%rdg + 3dgt)	±(1.0%rdg + 3dgt)	±(1.0%rdg + 2dgt)	±(0.8%rdg + 2dgt)
Buzzer:	<120Ω	<120Ω	<140Ω	<35Ω
Frequency				
Measurement range:			0.01Hz÷99.99kHz	1Hz÷40.00kHz
Basic accuracy:			±(1.5%rdg + 5dgt)	±(0.1%rdg + 2dgt)
Capacitance				
Measurement range:			0.001nF ÷ 100µF	0.001nF ÷ 100mF
Basic accuracy:			±(3.0%rdg + 5dgt)	±(2.0%rdg + 8dgt)
Duty Cycle				
Measurement range:			20% ÷ 80%	
Basic accuracy:			±(1.0%rdg + 5dgt)	
Temperat. with type K probe				
Measurement range:			-40°C ÷ 800°C	
Basic accuracy:			±(2.0%rdg + 3dgt)	

53

ACCESSORIES	Code
Standard	
Couple of test leads	4413-2
Carrying bag	B80
Batteries	
User manual	
Optional	
Adapter for type K probes (only HT322)	T10
Type K probes (only HT322)	



HT321
HR000321



HT322
HR000322



HT327
HR000327



HT326
HR000326



宇宏企業股份有限公司

台北：三重區重新路五段609巷16號6樓之1 新竹：新竹縣竹北市台元26號4樓之10
TEL:02-22782269 FAX:02-22782059 TEL:03-552-6779 FAX:03-552-6739
http://www.fluke-tekrnix.tw http://www.radiotek.com.tw



1. ELECTRICAL SPECIFICATIONS

Accuracy is indicated as \pm (%rdg + numbers of digits) at 23°C \pm 5°C, <75%HR

DC VOLTAGE

Range	Resolution	Accuracy	Overload protection
400.0mV	0.1mV	$\pm(0.5\%rdg+2dgt)$	1000VDC 750VACrms
4.000V	0.001V	$\pm(0.5\%rdg+2dgt)$	
40.00V	0.01V		
400.0V	0.1V		
1000V	1V	$\pm(1.0\%rdg+2dgt)$	

Input impedance: 10M Ω // <100pF

AC TRMS VOLTAGE

Range	Resolution	Accuracy (45 ÷ 400Hz)	Overload protection
400.0mV	0.1mV	Not specified	1000VDC 750VACrms
4.000V	0.001V	$\pm(1.3\%rdg+5dgt)$ (50 ÷ 300Hz)	
40.00V	0.01V	$\pm(1.2\%rdg+5dgt)$ (50 ÷ 500Hz)	
400.0V	0.1V		
750V	1V		

Input impedance: 10M Ω // <100pF

DC CURRENT

Range	Resolution	Accuracy	Voltage drop	Overload protection
400.0 μ A	0.1 μ A	$\pm(1.0\%rdg+2dgt)$	<5mV/ μ A	600VACrms
4000 μ A	1 μ A		2Vmax	Fuse 10A/1000V
10.00A	0.01A			

AC TRMS CURRENT

Range	Resolution	Accuracy (50÷500Hz)	Voltage drop	Overload protection
400.0 μ A	0.1 μ A	Not declared	2Vmax	600VACrms
4000 μ A	1 μ A			Fuse 10A/1000V
10.00A	0.01A	$\pm(1.5\%rdg + 5dgt)$ (50÷399Hz) $\pm(2.0\%rdg + 5dgt)$ (400÷500Hz)		

RESISTANCE

Range	Resolution	Accuracy	Open voltage	Overload protection
400.0 Ω	0.1 Ω	$\pm(1.0\%rdg+5dgt)$	about 0.45V	600VACrms
4.000k Ω	0.001k Ω	$\pm(0.7\%rdg+2dgt)$		
40.00k Ω	0.01k Ω			
400.0k Ω	0.1k Ω			
4.000M Ω	0.001M Ω	$\pm(1.0\%rdg+2dgt)$		
40.00M Ω	0.01M Ω	$\pm(1.5\%rdg+5dgt)$		





DIODE TEST

Range	Resolution	Accuracy	Open voltage	Overload protection
	10mV	$\pm(1.5\%rdg+5dgt)$	<3VDC	600VACrms

TEST CONTINUITY

Range	Buzzer	Open voltage	Overload protection
	R<35Ω	about 0.5VDC	600VACrms

FREQUENCY

Range	Resolution	Accuracy	SensitivITÀ	Overload protection
4.000kHz	0.001kHz	$\pm(0.01\%rdg+1dgt)$	>1.5VACrms <5VACrms	600VACrms
40.00kHz	0.01kHz			
400.0kHz	0.1kHz			
4.000MHz	0.001MHz			
40.00MHz	0.01MHz	Not declared	>2VACrms <5VACrms	
400.0MHz	0.1MHz			

Minimum pulse duration: 25ns
30% ≤ Duty Cycle ≤ 70%

CAPACITANCE

Range	Resolution	Accuracy	Overload protection
4.000nF	0.001nF	$\pm(3.0\%rdg+10dgt)$	600VACrms
40.00nF	0.01nF	$\pm(2.0\%rdg+8dgt)$	
400.0nF	0.1nF		
4.000μF	0.001μF		
40.00μF	0.01μF		
400.0μF	0.1μF		
4.000mF	0.001mF	$\pm(5.0\%rdg+20dgt)$	
40.00mF	0.01mF		



2. GENERAL SPECIFICATIONS


Display:

- LCD display, 4 digit with maximum reading 3999 counts with sign and decimal point and bargraph
- Automatic polarity indication
- Backlight
- "OL" over range indication

Features:

- HOLD
- MX/MN for maximum and minimum value
- RANGE for manual selection
- REL for relative measurements
- PK for peak measurements
- Auto Power OFF after 30 minutes of don't work

Low battery indication:

- The symbol "  " appears when the battery voltage is low

Operating temperature:

- 0°C to 40°C, <80%HR

Storage temperature:

- -20°C to 60°C, <70%HR

General informations:

- Altitude max: 2000m
- Pollution degree: 2
- Insulation: double insulation

Power supply:

- 1 x 9V alkaline battery type NEDA1604, JIS006P, IEC6F22

Sizes:

- 163(L)x88(W)x48(H) mm

Weight (included batteries):

- 400g

Applied standards:

- LVD: EN 61010-1 CAT IV 600V – CAT III 1000V
- EMC: EN60326

This product conforms to the prescriptions of the European directive on low voltage 2006/95/EEC and to EMC directive 2004/108/EEC

